

**Description**

Fastener Length: 23/32", Thread: 10-32, Thread Length: 11/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	ST3M506361
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-045-4298
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N ST3M506-3-6-1 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.306 Inches Minimum And 0.356 Inches Maximum
<b>Fastener Length:</b>	0.691 Inches Minimum And 0.721 Inches Maximum
<b>Head Style:</b>	Oval Countersunk
<b>Head Diameter:</b>	0.327 Inches Minimum And 0.332 Inches Maximum
<b>Shoulder Diameter:</b>	0.2177 Inches Minimum First Shoulder And 0.2182 Inches Maximum First Shoulder
<b>Shoulder Length:</b>	0.315 Inches Minimum First Shoulder And 0.343 Inches Maximum First Shoulder
<b>Internal Drive Style:</b>	High-torque
<b>Nominal Thread Diameter:</b>	0.190 Inches
<b>Thread Quantity Per Inch:</b>	32
<b>Countersink Angle:</b>	99.0 Degrees Minimum And 101.0 Degrees Maximum
<b>Shoulder Shape:</b>	Round First Shoulder
<b>Special Features:</b>	Socket Drive Recess In Thread End 0.0791 In. Min And 0.0806 In. Max Width Across Flats
<b>Material:</b>	Steel Comp Xm-13 Overall
<b>Material Document And Classification:</b>	Ams5629 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M506-3-6-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.