

P/N ST3M506-3-9-1

Description

Fastener Length: 29/32", Thread: 10-32, Thread Length: 11/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: ST3M506391

Minimum Qty (MOQ): 1 EA

NSN: 5305-01-045-4299

Schedule B: 7318.15.6080

ECCN: EAR99

National Motor Freight: 093490, Bolt / Nut / Screw / Clips / Fastener / Etc



^{*} See page 2 for technical characteristics

P/N ST3M506-3-9-1 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.306 Inches Minimum And 0.356 Inches Maximum
Fastener Length:	0.878 Inches Minimum And 0.908 Inches Maximum
Head Style:	Oval Countersunk
Head Diameter:	0.327 Inches Minimum And 0.332 Inches Maximum
Shoulder Diameter:	0.217 Inches Minimum First Shoulder And 0.218 Inches Maximum First Shoulder
Shoulder Length:	0.502 Inches Minimum First Shoulder And 0.530 Inches Maximum First Shoulder
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Thread Quantity Per Inch:	32
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Shoulder Shape:	Round First Shoulder
Special Features:	Socket Drive Recess In Thd End 0.079 In. Min,0.080 In. Max Width Across Fats
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams 5629 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting https://military-fasteners.com/screws/machine+screws/ST3M506-3-9-1 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.