

Description

Fastener Length: 1-15/64", Thread: 1/4-28, Thread Length: 25/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | ST3M5064131 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5305-01-046-5454 |
| Schedule B: | 7318.15.6080 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

P/N ST3M506-4-13-1 Specifications

| | |
|----------------------------------|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.397 Inches Nominal |
| Fastener Length: | 1.193 Inches Minimum And 1.240 Inches Maximum |
| Head Style: | Fillister Countersunk |
| Head Diameter: | 0.4208 Inches Minimum And 0.4258 Inches Maximum |
| Head Height: | 0.015 Inches Maximum |
| Internal Drive Style: | High-torque |
| Nominal Thread Diameter: | 0.250 Inches |
| Thread Quantity Per Inch: | 28 |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Steel Corrosion Resisting Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M506-4-13-1> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.