

Description

Fastener Length: 47/64", Thread: 1/4-24, Thread Length: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M50654
Minimum Qty (MOQ):	1 EA
NSN:	5305-01-046-5442
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

P/N ST3M506-5-4 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.441 Inches Minimum And 0.508 Inches Maximum
Fastener Length:	0.701 Inches Minimum And 0.748 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.461 Inches Minimum And 0.507 Inches Maximum
Shoulder Diameter:	0.342 Inches Minimum First Shoulder And 0.343 Inches Maximum First Shoulder
Shoulder Length:	0.240 Inches Minimum First Shoulder And 0.260 Inches Maximum First Shoulder
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.312 Inches
Thread Quantity Per Inch:	24
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Shoulder Shape:	Round First Shoulder
Special Features:	Internal Hexagon Socket 0.127 In. Min And 0.130 In. Max Width Across Flats,0.160 In. Deep In Thread End
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams5629 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M506-5-4> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.