

Description

Fastener Length: 1-11/64", Thread: 3/8-24, Thread Length: 35/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M506610
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-046-5445
Schedule B:	7318.15.6080
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N ST3M506-6-10 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.490 Inches Minimum And 0.557 Inches Maximum
Fastener Length:	1.125 Inches Minimum And 1.172 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.542 Inches Minimum And 0.596 Inches Maximum
Shoulder Diameter:	0.4057 Inches Minimum First Shoulder
Shoulder Length:	0.615 Inches Minimum First Shoulder And 0.635 Inches Maximum First Shoulder
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.375 Inches
Thread Quantity Per Inch:	24
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Shoulder Shape:	Round First Shoulder
Special Features:	Internal Hexagon Socket 0.158 In. Min And 0.162 In. Max Width Across Flats,0.190 In. Deep In Thread End
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams5629 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M506-6-10> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.