

Description

Thread Size: 3/8"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	ST3M525N6ME
Minimum Qty (MOQ):	5 EA
NSN:	5320-00-286-0663
Schedule B:	7616.10.1000
ECCN:	EAR99
National Motor Freight:	013630, Alum Rivets

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N ST3M525N6ME Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.622 Inches Minimum And 0.628 Inches Maximum
Collar Overall Height:	0.640 Inches Minimum And 0.660 Inches Maximum
Lubrication:	Cetyl Alcohol
Collar Inside Diameter:	0.387 Inches Minimum And 0.393 Inches Maximum
Nominal Thread Size:	0.375 Inches
Collar Style:	Threaded (break Off) Type
Heat Treatment:	T-6 Solution Heat Treated Overall
Material:	Aluminum Alloy 2024 Overall
Material Document And Classification:	Qq-a-430 Fed Spec Single Material Response Overall Or Qq-a-225/6 Fed Spec Single Material Response Overall
Surface Treatment:	Anodize Overall
Surface Treatment Document And Classification:	Mil-a-8625 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/ST3M525N6ME and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.