

**Description**

Fastener Length: 6-3/16", Thread: 3/4-16, Thread Length: 1-1/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	ST3M5711282
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-324-7716
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N ST3M571-12-82 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.027 Inches Minimum And 1.077 Inches Maximum
<b>Fastener Length:</b>	6.162 Inches Minimum And 6.192 Inches Maximum
<b>Head Style:</b>	Dished Hexagon
<b>Head Height:</b>	0.701 Inches Minimum And 0.721 Inches Maximum
<b>Width Between Flats:</b>	0.803 Inches Minimum And 0.814 Inches Maximum
<b>Extended Washer Diameter:</b>	1.220 Inches Minimum And 1.230 Inches Maximum
<b>Extended Washer Thickness:</b>	0.168 Inches Minimum And 0.188 Inches Maximum
<b>Grip Diameter:</b>	0.7485 Inches Minimum And 0.7490 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.750 Inches
<b>Grip Length:</b>	5.115 Inches Minimum And 5.135 Inches Maximum
<b>Thread Quantity Per Inch:</b>	16
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M571-12-82> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.