

P/N ST3M571-12-82

Description

Fastener Length: 6-3/16", Thread: 3/4-16, Thread Length: 1-1/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: ST3M5711282

Minimum Qty (MOQ): 1 EA

NSN: 5306-00-324-7716

Schedule B: 7318.15.8085

ECCN: 9A991

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N ST3M571-12-82 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.027 Inches Minimum And 1.077 Inches Maximum
Fastener Length:	6.162 Inches Minimum And 6.192 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.701 Inches Minimum And 0.721 Inches Maximum
Width Between Flats:	0.803 Inches Minimum And 0.814 Inches Maximum
Extended Washer Diameter:	1.220 Inches Minimum And 1.230 Inches Maximum
Extended Washer Thickness:	0.168 Inches Minimum And 0.188 Inches Maximum
Grip Diameter:	0.7485 Inches Minimum And 0.7490 Inches Maximum
Nominal Thread Diameter:	0.750 Inches
Grip Length:	5.115 Inches Minimum And 5.135 Inches Maximum
Thread Quantity Per Inch:	16
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/ST3M571-12-82 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.