

Description


Fastener Length: 1-15/32", Thread: 1/4-28, Thread Length: 31/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M571416
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-285-9933
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N ST3M571-4-16 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.443 Inches Minimum And 0.493 Inches Maximum
Fastener Length:	1.453 Inches Minimum And 1.483 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.290 Inches Minimum And 0.310 Inches Maximum
Width Between Flats:	0.304 Inches Minimum And 0.313 Inches Maximum
Extended Washer Diameter:	0.428 Inches Minimum And 0.438 Inches Maximum
Extended Washer Thickness:	0.059 Inches Minimum And 0.079 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.990 Inches Minimum And 1.010 Inches Maximum
Thread Quantity Per Inch:	28
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M571-4-16> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.