

Description

Fastener Length: 27/32", Hole Diameter: ", Thread: 1/4-28, Thread Length: 31/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | ST3M5714H6 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5306-01-021-6838 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N ST3M571-4H6 Specifications

| | |
|--|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.443 Inches Minimum And 0.493 Inches Maximum |
| Fastener Length: | 0.828 Inches Minimum And 0.858 Inches Maximum |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.290 Inches Minimum And 0.310 Inches Maximum |
| Width Between Flats: | 0.304 Inches Minimum And 0.313 Inches Maximum |
| Extended Washer Diameter: | 0.428 Inches Minimum And 0.438 Inches Maximum |
| Extended Washer Thickness: | 0.059 Inches Minimum And 0.079 Inches Maximum |
| Hole Diameter: | 0.055 Inches Nominal |
| Grip Diameter: | 0.2490 Inches Minimum And 0.2495 Inches Maximum |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.365 Inches Minimum And 0.385 Inches Maximum |
| Hole Quantity: | 4 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 28 |
| Minimum Tensile Strength: | 220000 Pounds Per Square Inch |
| Hole Configuration Style: | Double Hexagon Longitudinal Hole |
| Material: | Steel Overall |
| Material Document And Classification: | 23-112,mcdonnell Douglas Corp Mfr Ref Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M571-4H6> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.