

Description

Fastener Length: 1-1/4", Thread: 1/4-24, Thread Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M571511
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-286-0198
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N ST3M571-5-11 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.526 Inches Minimum And 0.576 Inches Maximum
Fastener Length:	1.224 Inches Minimum And 1.254 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.338 Inches Minimum And 0.358 Inches Maximum
Width Between Flats:	0.367 Inches Minimum And 0.376 Inches Maximum
Extended Washer Diameter:	0.516 Inches Minimum And 0.536 Inches Maximum
Extended Washer Thickness:	0.072 Inches Minimum And 0.092 Inches Maximum
Grip Diameter:	0.3115 Inches Minimum And 0.3120 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	0.678 Inches Minimum And 0.698 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M571-5-11> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.