



Military-Fasteners.com

P/N ST3M571-5D21

## Description

Fastener Length: 1-7/8", Thread: 1/4-24, Thread Length: 37/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	ST3M5715D21
Minimum Qty (MOQ):	1 EA
NSN:	5306-00-281-7172
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N ST3M571-5D21 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.516 Inches Minimum And 0.586 Inches Maximum
<b>Fastener Length:</b>	1.838 Inches Minimum And 1.888 Inches Maximum
<b>Head Style:</b>	Double Hexagon W/hole
<b>Head Height:</b>	0.338 Inches Minimum And 0.358 Inches Maximum
<b>Width Between Flats:</b>	0.367 Inches Minimum And 0.376 Inches Maximum
<b>Extended Washer Diameter:</b>	0.521 Inches Minimum And 0.531 Inches Maximum
<b>Extended Washer Thickness:</b>	0.072 Inches Minimum And 0.092 Inches Maximum
<b>Grip Diameter:</b>	0.3115 Inches Minimum And 0.3120 Inches Maximum
<b>Shank Unthreaded Hole Diameter:</b>	0.076 Inches Minimum First Hole And 0.081 Inches Maximum First Hole
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Grip Length:</b>	1.302 Inches Minimum And 1.322 Inches Maximum
<b>Thread Quantity Per Inch:</b>	24
<b>Minimum Tensile Strength:</b>	220000 Pounds Per Square Inch
<b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b>	1.630 Inches Minimum First Hole And 1.690 Inches Maximum First Hole
<b>Material:</b>	Steel Corrosion Resisting Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M571-5D21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.