

Description

Fastener Length: 1-7/8", Thread: 1/4-24, Thread Length: 37/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | ST3M5715D21 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-00-281-7172 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N ST3M571-5D21 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.516 Inches Minimum And 0.586 Inches Maximum |
| Fastener Length: | 1.838 Inches Minimum And 1.888 Inches Maximum |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.338 Inches Minimum And 0.358 Inches Maximum |
| Width Between Flats: | 0.367 Inches Minimum And 0.376 Inches Maximum |
| Extended Washer Diameter: | 0.521 Inches Minimum And 0.531 Inches Maximum |
| Extended Washer Thickness: | 0.072 Inches Minimum And 0.092 Inches Maximum |
| Grip Diameter: | 0.3115 Inches Minimum And 0.3120 Inches Maximum |
| Shank Unthreaded Hole Diameter: | 0.076 Inches Minimum First Hole And 0.081 Inches Maximum First Hole |
| Nominal Thread Diameter: | 0.312 Inches |
| Grip Length: | 1.302 Inches Minimum And 1.322 Inches Maximum |
| Thread Quantity Per Inch: | 24 |
| Minimum Tensile Strength: | 220000 Pounds Per Square Inch |
| Distance From Head Largest Bearing Surface To Shank Hole Center: | 1.630 Inches Minimum First Hole And 1.690 Inches Maximum First Hole |
| Material: | Steel Corrosion Resisting Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M571-5D21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.