

**Description**

Fastener Length: 2-7/8", Thread: 1/4-24, Thread Length: 37/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | ST3M5715D37                               |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-00-281-7468                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N ST3M571-5D37 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>  | Right-hand  |
| <b>Thread Length:</b>   | 0.516 Inches Minimum And 0.586 Inches Maximum                       |
| <b>Fastener Length:</b>   | 2.838 Inches Minimum And 2.888 Inches Maximum                       |
| <b>Head Style:</b>  | Double Hexagon W/hole   |
| <b>Head Height:</b>   | 0.338 Inches Minimum And 0.358 Inches Maximum                       |
| <b>Width Between Flats:</b>   | 0.367 Inches Minimum And 0.376 Inches Maximum                       |
| <b>Extended Washer Diameter:</b>  | 0.521 Inches Minimum And 0.531 Inches Maximum                       |
| <b>Extended Washer Thickness:</b>                                       | 0.072 Inches Minimum And 0.092 Inches Maximum                       |
| <b>Grip Diameter:</b>   | 0.3115 Inches Minimum And 0.3120 Inches Maximum                     |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.076 Inches Minimum First Hole And 0.081 Inches Maximum First Hole |
| <b>End Item Identification:</b>   | Aircraft, Eagle F-15  |
| <b>Nominal Thread Diameter:</b>   | 0.312 Inches  |
| <b>Grip Length:</b>   | 2.302 Inches Minimum And 2.322 Inches Maximum                       |
| <b>Thread Quantity Per Inch:</b>  | 24  |
| <b>Minimum Tensile Strength:</b>  | 220000 Pounds Per Square Inch                                       |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 2.630 Inches Minimum First Hole And 2.690 Inches Maximum First Hole |
| <b>Material:</b>  | Steel Corrosion Resisting Overall                                   |
| <b>Surface Treatment:</b>   | Passivate Overall   |
| <b>Thread Series Designator:</b>  | Unjf  |
| <b>Specification/standard Data:</b>                                     | 76301-st3-571 Manufacturers Standard                                |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M571-5D37> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.