

**Description**

Fastener Length: 1-1/2", Thread: 3/8-24, Thread Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | ST3M5716D14                               |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-00-280-3333                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N ST3M571-6D14 Specifications

|   |   |
|---|---|
| <b>Thread Class:</b>  | 3a  |
| <b>Thread Direction:</b>  | Right-hand  |
| <b>Thread Length:</b>   | 0.589 Inches Minimum And 0.639 Inches Maximum                       |
| <b>Fastener Length:</b>   | 1.474 Inches Minimum And 1.504 Inches Maximum                       |
| <b>Head Style:</b>  | Double Hexagon W/hole   |
| <b>Head Height:</b>   | 0.378 Inches Minimum And 0.398 Inches Maximum                       |
| <b>Width Between Flats:</b>   | 0.430 Inches Minimum And 0.439 Inches Maximum                       |
| <b>Extended Washer Diameter:</b>  | 0.639 Inches Minimum And 0.649 Inches Maximum                       |
| <b>Extended Washer Thickness:</b>                                       | 0.081 Inches Minimum And 0.101 Inches Maximum                       |
| <b>Grip Diameter:</b>   | 0.3740 Inches Minimum And 0.3745 Inches Maximum                     |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.106 Inches Minimum First Hole And 0.111 Inches Maximum First Hole |
| <b>Nominal Thread Diameter:</b>   | 0.375 Inches  |
| <b>Grip Length:</b>   | 0.865 Inches Minimum And 0.885 Inches Maximum                       |
| <b>Thread Quantity Per Inch:</b>  | 24  |
| <b>Minimum Tensile Strength:</b>  | 220000 Pounds Per Square Inch                                       |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 1.251 Inches Minimum First Hole And 1.291 Inches Maximum First Hole |
| <b>Material:</b>  | Steel Corrosion Resisting Overall                                   |
| <b>Surface Treatment:</b>   | Passivate Overall   |
| <b>Thread Series Designator:</b>  | Unjf  |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M571-6D14> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.