

## P/N ST3M571-6H23

### **Description**

Fastener Length: 2-1/16", Hole Diameter: ", Thread: 3/8-24, Thread Length: 5/8"

\* Manufacturer certifications are shipped with your order FREE of charge

## Order this part online

#### **Additional Information**

SKU / Model: ST3M5716H23

Minimum Qty (MOQ): 1 EA

NSN: 5306-00-326-4625

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



<sup>\*</sup> See page 2 for technical characteristics

# P/N ST3M571-6H23 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.589 Inches Minimum And 0.639 Inches Maximum
Fastener Length:	2.037 Inches Minimum And 2.067 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.378 Inches Minimum And 0.398 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Extended Washer Diameter:	0.639 Inches Minimum And 0.649 Inches Maximum
Extended Washer Thickness:	0.081 Inches Minimum And 0.101 Inches Maximum
Hole Diameter:	0.055 Inches Nominal
Grip Diameter:	0.3740 Inches Minimum And 0.3745 Inches Maximum
Nominal Thread Diameter:	0.375 Inches
Grip Length:	1.428 Inches Minimum And 1.448 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Hole Configuration Style:	Hexagon Longitudinal Hole
Material:	Steel Corrosion Resisting Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this bolt from our inventory online by visiting <a href="https://military-fasteners.com/bolts/machine+bolts/ST3M571-6H23">https://military-fasteners.com/bolts/machine+bolts/ST3M571-6H23</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.