

P/N ST3M571-7H28

Description

Fastener Length: 2-15/32", Hole Diameter: ", Thread: 3/8-20, Thread Length: 23/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model: ST3M5717H28

Minimum Qty (MOQ): 1 EA

NSN: 5306-00-324-7712

Schedule B: 7318.15.8085

ECCN: EAR99

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N ST3M571-7H28 Specifications

| Thread Class: | 3a |
|----------------------------|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.680 Inches Minimum And 0.730 Inches Maximum |
| Fastener Length: | 2.440 Inches Minimum And 2.470 Inches Maximum |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.425 Inches Minimum And 0.445 Inches Maximum |
| Width Between Flats: | 0.492 Inches Minimum And 0.502 Inches Maximum |
| Extended Washer Diameter: | 0.740 Inches Minimum And 0.750 Inches Maximum |
| Extended Washer Thickness: | 0.089 Inches Minimum And 0.109 Inches Maximum |
| Hole Diameter: | 0.055 Inches Nominal |
| Grip Diameter: | 0.4365 Inches Minimum And 0.4370 Inches Maximum |
| Nominal Thread Diameter: | 0.437 Inches |
| Grip Length: | 1.740 Inches Minimum And 1.760 Inches Maximum |
| Hole Quantity: | 4 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 20 |
| Hole Configuration Style: | Hexagon Longitudinal Hole |
| Material: | Steel Corrosion Resisting Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unjf |
| | |

How to Order

Order this bolt from our inventory online by visiting https://military-fasteners.com/bolts/machine+bolts/ST3M571-7H28 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out here to complete your order.