

P/N ST3M571-8-12

Military-Fasteners.com

Description

Fastener Length: 1-17/32", Thread: 1/2-20, Thread Length: 25/32"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

| SKU / Model: | ST3M571812 |
|-------------------------|---|
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-00-352-0465 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



P/N ST3M571-8-12 Specifications

| Thread Class: | 3a |
|----------------------------|---|
| Thread Direction: | Right-hand |
| Thread Length: | 0.742 Inches Minimum And 0.792 Inches Maximum |
| Fastener Length: | 1.502 Inches Minimum And 1.532 Inches Maximum |
| Head Style: | Double Hexagon W/hole |
| Head Height: | 0.494 Inches Minimum And 0.514 Inches Maximum |
| Width Between Flats: | 0.553 Inches Minimum And 0.564 Inches Maximum |
| Extended Washer Diameter: | 0.818 Inches Minimum And 0.828 Inches Maximum |
| Extended Washer Thickness: | 0.113 Inches Minimum And 0.133 Inches Maximum |
| Grip Diameter: | 0.4990 Inches Minimum And 0.4995 Inches Maximum |
| Nominal Thread Diameter: | 0.500 Inches |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 220000 Pounds Per Square Inch |
| Material: | Steel Corrosion Resisting Overall |
| Surface Treatment: | Passivate Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <u>https://military-fasteners.com/bolts/machine+bolts/ST3M571-8-12</u> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <u>here</u> to complete your order.