

Description

Fastener Length: 3-21/32", Hole Diameter: ", Thread: 1/2-20, Thread Length: 25/32

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M5718H46
Minimum Qty (MOQ):	1
NSN:	5306-01-021-6839
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N ST3M571-8H46 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.742 Inches Minimum And 0.792 Inches Maximum
Fastener Length:	3.627 Inches Minimum And 3.657 Inches Maximum
Head Style:	Double Hexagon W/hole
Head Height:	0.494 Inches Minimum And 0.514 Inches Maximum
Width Between Flats:	0.553 Inches Minimum And 0.564 Inches Maximum
Extended Washer Diameter:	0.818 Inches Minimum And 0.828 Inches Maximum
Extended Washer Thickness:	0.113 Inches Minimum And 0.133 Inches Maximum
Hole Diameter:	0.055 Inches Nominal
Grip Diameter:	0.4990 Inches Minimum And 0.4995 Inches Maximum
Nominal Thread Diameter:	0.500 Inches
Grip Length:	2.865 Inches Minimum And 2.885 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Hole Configuration Style:	Double Hexagon Longitudinal Hole
Material:	Steel Overall
Material Document And Classification:	23-112,mcdonnell Douglas Corp Mfr Ref Single Material Response Overall
Surface Treatment:	Passivate Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M571-8H46> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.