



Military-Fasteners.com

P/N ST3M714-4-7

Description

Fastener Length: 49/64", Thread: 1/4-28, Thread Length: 21/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M71447
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-147-4040
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N ST3M714-4-7 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.291 Inches Minimum And 0.341 Inches Maximum
Fastener Length:	0.739 Inches Minimum And 0.769 Inches Maximum
Head Style:	Flat Countersunk
Head Diameter:	0.497 Inches Minimum And 0.507 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.428 Inches Minimum And 0.448 Inches Maximum
Thread Quantity Per Inch:	28
Countersink Angle:	99.0 Degrees Minimum And 101.0 Degrees Maximum
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams 5629 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/machine+screws/ST3M714-4-7> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.