

Description

Fastener Length: 1-9/16", Thread: 1/4-28, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M735418
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-337-2306
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N ST3M735-4-18 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.308 Inches Minimum And 0.323 Inches Maximum
Fastener Length:	1.550 Inches Minimum And 1.570 Inches Maximum
Head Style:	Hexagon
Head Height:	0.126 Inches Minimum And 0.141 Inches Maximum
Width Between Flats:	0.422 Inches Minimum
Grip Diameter:	0.2483 Inches Minimum And 0.2492 Inches Maximum
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.132 Inches Nominal
Thread Quantity Per Inch:	28
Material:	Steel Comp 630 Locking Feature
Material:	Steel Overall
Material Document And Classification:	Ms 5643 Assn Std Single Material Response Locking Feature
Surface Treatment:	Cadmium Overall
Surface Treatment:	Passivate Locking Feature
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Locking Feature
Surface Treatment Document And Classification:	Qq-p-416, Type Ii, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M735-4-18> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.