

**Description**

Fastener Length: 1-63/64", Thread: 1/4-28, Thread Length: 21/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | ST3M735425                                |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-01-052-4450                          |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N ST3M735-4-25 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>  | 3a   |
| <b>Thread Direction:</b>  | Right-hand   |
| <b>Thread Length:</b>   | 0.283 Inches Minimum And 0.334 Inches Maximum                                  |
| <b>Fastener Length:</b>   | 1.981 Inches Minimum And 2.001 Inches Maximum                                  |
| <b>Head Style:</b>  | Dished Hexagon   |
| <b>Head Height:</b>   | 0.126 Inches Minimum And 0.141 Inches Maximum                                  |
| <b>Width Between Flats:</b>   | 0.430 Inches Minimum And 0.439 Inches Maximum                                  |
| <b>Grip Diameter:</b>   | 0.2483 Inches Minimum And 0.2492 Inches Maximum                                |
| <b>Shank Unthreaded Hole Diameter:</b>                                  | 0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole            |
| <b>Nominal Thread Diameter:</b>   | 0.250 Inches   |
| <b>Grip Length:</b>   | 1.562 Inches Minimum And 1.578 Inches Maximum                                  |
| <b>Thread Quantity Per Inch:</b>  | 28   |
| <b>Hardness Rating:</b>   | 36.0 Rockwell C Minimum Overall And 43.0 Rockwell C Maximum Overall            |
| <b>Distance From Head Largest Bearing Surface To Shank Hole Center:</b> | 1.881 Inches Minimum First Hole And 1.911 Inches Maximum First Hole            |
| <b>Surface Finish:</b>  | 63.0 Microinches Bearing Surface Of Head                                       |
| <b>Surface Finish:</b>  | 63.0 Microinches Grip  |
| <b>Special Features:</b>  | Retaining Element In Shank   |
| <b>Material:</b>  | Steel Comp E4340 Overall Or Steel Comp 4340 Overall Or Steel Comp 8740 Overall |
| <b>Surface Treatment:</b>   | Cadmium Overall And Chromate Overall   |
| <b>Surface Treatment Document And Classification:</b>                   | Qq-p-416,type 2,class 2 Fed Spec Single Treatment Response Overall             |
| <b>Thread Series Designator:</b>  | Unjf   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M735-4-25> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.