

Description

Fastener Length: 2-63/64", Thread: 1/4-28, Thread Length: 7/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M735441
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-121-0360
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N ST3M735-4-41 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.402 Inches Minimum And 0.438 Inches Maximum
Fastener Length:	2.980 Inches Minimum And 3.000 Inches Maximum
Head Style:	Dished Hexagon
Head Height:	0.126 Inches Minimum And 0.141 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2483 Inches Minimum And 0.2492 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.086 Inches Maximum First Hole
Nominal Thread Diameter:	0.250 Inches
Grip Length:	2.562 Inches Minimum And 2.578 Inches Maximum
Thread Quantity Per Inch:	28
Hardness Rating:	36.0 Rockwell C Minimum Overall And 41.0 Rockwell C Maximum Overall
Distance From Head Largest Bearing Surface To Shank Hole Center:	1.910 Inches Minimum First Hole And 2.880 Inches Maximum First Hole
Surface Finish:	63.0 Microinches Grip
Surface Finish:	63.0 Microinches Threads
Special Features:	Detent Ring In Shank
Material:	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Or Steel Comp 6150 Overall
Surface Treatment:	Cadmium Overall And Chromate Overall
Surface Treatment Document And Classification:	Qq-p-416 Ty 2 Cl 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M735-4-41> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.