

Description

Fastener Length: 3-13/32", Thread: 1/4-28, Thread Length: 5/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M735448
Minimum Qty (MOQ):	1
NSN:	5306-01-406-3702
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N ST3M735-4-48 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.308 Inches Minimum And 0.323 Inches Maximum
Fastener Length:	3.394 Inches Minimum And 3.414 Inches Maximum
Head Style:	Hexagon
Head Height:	0.128 Inches Minimum And 0.141 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Locking Feature:	Slotted Ring
Grip Diameter:	0.2483 Inches Minimum And 0.2492 Inches Maximum
End Item Identification:	F-15s
Nominal Thread Diameter:	0.250 Inches
Grip Length:	2.976 Inches Minimum And 2.992 Inches Maximum
Thread Quantity Per Inch:	28
Hardness Rating:	36.0 Rockwell C Minimum Overall And 41.0 Rockwell C Maximum Overall
Material:	Steel Comp 630 Ring And Steel Comp 631 Ring
Material:	Steel Overall
Material Document And Classification:	Ams5643 Assn Std 1st Material Response Ring Or Ams5673 Assn Std 2nd Material Response Ring
Surface Treatment:	Cadmium Overall
Surface Treatment:	Passivate Ring
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Ring
Surface Treatment Document And Classification:	Qq-p-416,type 2, Class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M735-4-48> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.