

P/N ST3M735-4-50

Description

Fastener Length: 3-9/16", Thread: 1/4-28, Thread Length: 5/16"

* Manufacturer certifications are shipped with your order <u>FREE</u> of charge

Order this part online

Additional Information

SKU / Model: ST3M735450

Minimum Qty (MOQ): 1 EA

NSN: 5306-01-452-4591

National Motor Freight: 093486, Bolts, nuts Or Screws, Noi (sub 3)



^{*} See page 2 for technical characteristics

P/N ST3M735-4-50 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.308 Inches Minimum And 0.323 Inches Maximum
Fastener Length:	3.543 Inches Minimum And 3.563 Inches Maximum
Head Style:	Hexagon
Head Height:	0.105 Inches Minimum And 0.120 Inches Maximum
Width Between Flats:	0.430 Inches Minimum And 0.439 Inches Maximum
Grip Diameter:	0.2483 Inches Minimum And 0.2492 Inches Maximum
End Item Identification:	F-15s
Nominal Thread Diameter:	0.250 Inches
Grip Length:	3.125 Inches Minimum And 3.141 Inches Maximum
Thread Quantity Per Inch:	28
Hardness Rating:	36.0 Rockwell C Minimum Fastener And 41.0 Rockwell C Maximum Fastener
Part Name Assigned By Controlling Agency:	Bolt, close Toler
Special Features:	Double Shear Strength 9,300 Lbs:ultimate Tensile Strength 4,680 Lbs
Material:	Steel Comp 630 Ring Or Steel Comp 631 Ring
Material:	Steel Comp E4340 Overall Or Steel Comp 4140 Overall Or Steel Comp 8740 Overall Or Steel Comp 4130 Overall Or Steel Comp 6150 Overall
Material Document And Classification:	Ams 5643 Assn Std 1st Material Response Ring Or Ams 5673 Assn Std 2nd Material Response Ring
Material Document And Classification:	Mil-s-5000 Mil Std 1st Material Response Overall Or Mil-s-5626 Mil Std 2nd Material Response Overall Or Mil-s-6049 Mil Std 3rd Material Response Overall Or Mil-s-6758 Mil Std 4th Material Response Overall Or Mil-s-8503 Mil Std 5th Material Response Overall
Surface Treatment:	Cadmium Overall
Surface Treatment:	Passivate Ring
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Ring
Surface Treatment Document And Classification:	Qq-p-416, Type Ii,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

