



Military-Fasteners.com

P/N ST3M753-12-86

## Description

Fastener Length: 6-7/16", Thread: 3/4-16, Thread Length: 1-1/16"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	ST3M7531286
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-186-9273
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



\* See page 2 for technical characteristics

## P/N ST3M753-12-86 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	1.027 Inches Minimum And 1.077 Inches Maximum
<b>Fastener Length:</b>	6.412 Inches Minimum And 6.442 Inches Maximum
<b>Head Style:</b>	Spline Extended Washer
<b>Head Height:</b>	0.472 Inches Minimum And 0.512 Inches Maximum
<b>Extended Washer Diameter:</b>	1.384 Inches Minimum And 1.394 Inches Maximum
<b>Extended Washer Thickness:</b>	0.098 Inches Minimum And 0.118 Inches Maximum
<b>Grip Diameter:</b>	0.7480 Inches Minimum And 0.7490 Inches Maximum
<b>Head Minor Diameter:</b>	0.797 Inches Minimum And 0.812 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.750 Inches
<b>Grip Length:</b>	5.365 Inches Minimum And 5.385 Inches Maximum
<b>Thread Quantity Per Inch:</b>	16
<b>Minimum Tensile Strength:</b>	220000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp Xm-13 Overall
<b>Material Document And Classification:</b>	Ams5629 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M753-12-86> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.