



Military-Fasteners.com

P/N ST3M753-12-86

Description

Fastener Length: 6-7/16", Thread: 3/4-16, Thread Length: 1-1/16"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M7531286
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-186-9273
Schedule B:	7318.15.2091
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N ST3M753-12-86 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.027 Inches Minimum And 1.077 Inches Maximum
Fastener Length:	6.412 Inches Minimum And 6.442 Inches Maximum
Head Style:	Spline Extended Washer
Head Height:	0.472 Inches Minimum And 0.512 Inches Maximum
Extended Washer Diameter:	1.384 Inches Minimum And 1.394 Inches Maximum
Extended Washer Thickness:	0.098 Inches Minimum And 0.118 Inches Maximum
Grip Diameter:	0.7480 Inches Minimum And 0.7490 Inches Maximum
Head Minor Diameter:	0.797 Inches Minimum And 0.812 Inches Maximum
Nominal Thread Diameter:	0.750 Inches
Grip Length:	5.365 Inches Minimum And 5.385 Inches Maximum
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams5629 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M753-12-86> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.