

Description

Fastener Length: 6-7/16", Thread: 3/4-16, Thread Length: 1-1/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | ST3M7531286 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-186-9273 |
| Schedule B: | 7318.15.2091 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE
AVAILABLE

P/N ST3M753-12-86 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 1.027 Inches Minimum And 1.077 Inches Maximum |
| Fastener Length: | 6.412 Inches Minimum And 6.442 Inches Maximum |
| Head Style: | Spline Extended Washer |
| Head Height: | 0.472 Inches Minimum And 0.512 Inches Maximum |
| Extended Washer Diameter: | 1.384 Inches Minimum And 1.394 Inches Maximum |
| Extended Washer Thickness: | 0.098 Inches Minimum And 0.118 Inches Maximum |
| Grip Diameter: | 0.7480 Inches Minimum And 0.7490 Inches Maximum |
| Head Minor Diameter: | 0.797 Inches Minimum And 0.812 Inches Maximum |
| Nominal Thread Diameter: | 0.750 Inches |
| Grip Length: | 5.365 Inches Minimum And 5.385 Inches Maximum |
| Thread Quantity Per Inch: | 16 |
| Minimum Tensile Strength: | 220000 Pounds Per Square Inch |
| Material: | Steel Comp Xm-13 Overall |
| Material Document And Classification: | Ams5629 Assn Std Single Material Response Overall |
| Surface Treatment: | Passivate Overall |
| Surface Treatment Document And Classification: | Qq-p-35 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M753-12-86> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.