

Description

Fastener Length: 3-1/2", Thread: 3/4-16, Thread Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M75312DD56
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-234-9403
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



P/N ST3M753-12DD56 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.927 Inches Minimum And 1.052 Inches Maximum
Fastener Length:	3.485 Inches Minimum And 3.515 Inches Maximum
Head Style:	Spline Extended Washer
Head Height:	0.472 Inches Minimum And 0.512 Inches Maximum
Width Between Flats:	0.222 Inches Minimum And 0.227 Inches Maximum
Extended Washer Diameter:	1.384 Inches Minimum And 1.394 Inches Maximum
Extended Washer Thickness:	0.098 Inches Minimum And 0.118 Inches Maximum
Grip Diameter:	0.9980 Inches Minimum And 0.9990 Inches Maximum
Shank Unthreaded Hole Diameter:	0.141 Inches Minimum All Holes And 0.146 Inches Maximum All Holes
Nominal Thread Diameter:	0.750 Inches
Grip Length:	2.438 Inches Minimum And 2.458 Inches Maximum
Thread Quantity Per Inch:	16
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	3.267 Inches Minimum All Holes And 3.307 Inches Maximum All Holes
Special Features:	Two Holes 90 Degrees Apart
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams 5629 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M753-12DD56> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.