

Description

Fastener Length: 6-25/32", Thread: 1/4-24, Thread Length: 1-43/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M753582
Minimum Qty (MOQ):	10 EA
NSN:	5306-01-212-0063
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N ST3M753-5-82 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.628 Inches Minimum And 1.678 Inches Maximum
Fastener Length:	6.763 Inches Minimum And 6.793 Inches Maximum
Head Style:	Spline Extended Washer
Head Height:	0.302 Inches Minimum And 0.322 Inches Maximum
Extended Washer Diameter:	0.575 Inches Minimum And 0.585 Inches Maximum
Extended Washer Thickness:	0.035 Inches Minimum And 0.055 Inches Maximum
Grip Diameter:	0.3115 Inches Minimum And 0.3120 Inches Maximum
Head Minor Diameter:	0.383 Inches Minimum And 0.389 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	5.115 Inches Minimum And 5.135 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams5629 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M753-5-82> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.