

Description

Fastener Length: 2-11/16", Thread: 1/4-24, Thread Length: 9/16"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	ST3M7535D33
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-186-0429
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N ST3M753-5D33 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.526 Inches Minimum And 0.576 Inches Maximum
Fastener Length:	2.661 Inches Minimum And 2.691 Inches Maximum
Head Style:	Spline Extended Washer
Head Height:	0.302 Inches Minimum And 0.322 Inches Maximum
Extended Washer Diameter:	0.575 Inches Minimum And 0.585 Inches Maximum
Extended Washer Thickness:	0.035 Inches Minimum And 0.055 Inches Maximum
Grip Diameter:	0.3115 Inches Minimum And 0.3120 Inches Maximum
Shank Unthreaded Hole Diameter:	0.076 Inches Minimum First Hole And 0.081 Inches Maximum First Hole
Head Minor Diameter:	0.360 Inches Minimum And 0.375 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	2.115 Inches Minimum And 2.135 Inches Maximum
Thread Quantity Per Inch:	24
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.453 Inches Minimum First Hole And 2.493 Inches Maximum First Hole
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams5629 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M753-5D33> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.