



Military-Fasteners.com

P/N ST3M753-5H27

Description

Fastener Length: 2-1/8", Hole Diameter: 3/64", Thread: 1/4-24, Thread Length: 0-63/64"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M7535H27
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-214-3476
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N ST3M753-5H27 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.975 Inches Minimum And 1.025 Inches Maximum
Fastener Length:	2.110 Inches Minimum And 2.140 Inches Maximum
Head Style:	Spline Extended Washer
Head Height:	0.247 Inches Minimum And 0.287 Inches Maximum
Width Between Flats:	0.360 Inches Minimum And 0.375 Inches Maximum
Extended Washer Diameter:	0.575 Inches Minimum And 0.585 Inches Maximum
Extended Washer Thickness:	0.035 Inches Minimum And 0.055 Inches Maximum
Hole Diameter:	0.050 Inches Minimum And 0.060 Inches Maximum
Grip Diameter:	0.3115 Inches Minimum And 0.3120 Inches Maximum
Nominal Thread Diameter:	0.312 Inches
Grip Length:	1.115 Inches Minimum And 1.135 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Thread Quantity Per Inch:	24
Hole Configuration Style:	Double Hexagon Flats
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams5629 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M753-5H27> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.