

**Description**

Fastener Length: 2-1/8", Hole Diameter: 3/64", Thread: 1/4-24, Thread Length: 0-63/64"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	ST3M7535H27
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-214-3476
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

## P/N ST3M753-5H27 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.975 Inches Minimum And 1.025 Inches Maximum
<b>Fastener Length:</b>	2.110 Inches Minimum And 2.140 Inches Maximum
<b>Head Style:</b>	Spline Extended Washer
<b>Head Height:</b>	0.247 Inches Minimum And 0.287 Inches Maximum
<b>Width Between Flats:</b>	0.360 Inches Minimum And 0.375 Inches Maximum
<b>Extended Washer Diameter:</b>	0.575 Inches Minimum And 0.585 Inches Maximum
<b>Extended Washer Thickness:</b>	0.035 Inches Minimum And 0.055 Inches Maximum
<b>Hole Diameter:</b>	0.050 Inches Minimum And 0.060 Inches Maximum
<b>Grip Diameter:</b>	0.3115 Inches Minimum And 0.3120 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.312 Inches
<b>Grip Length:</b>	1.115 Inches Minimum And 1.135 Inches Maximum
<b>Hole Quantity:</b>	4
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	24
<b>Hole Configuration Style:</b>	Double Hexagon Flats
<b>Material:</b>	Steel Comp Xm-13 Overall
<b>Material Document And Classification:</b>	Ams5629 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M753-5H27> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.