



Military-Fasteners.com

P/N ST3M753-7H16F

Description

Fastener Length: 1-23/32", Hole Diameter: 3/64", Thread: 7/16-20, Thread Length: 23/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | ST3M7537H16F |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5306-01-132-4786 |
| Schedule B: | 7318.15.8085 |
| ECCN: | 9A991 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N ST3M753-7H16F Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.680 Inches Minimum And 0.730 Inches Maximum |
| Fastener Length: | 1.690 Inches Minimum And 1.720 Inches Maximum |
| Head Style: | Spline Extended Washer |
| Head Height: | 0.310 Inches Minimum And 0.350 Inches Maximum |
| Width Between Flats: | 0.514 Inches Minimum And 0.605 Inches Maximum |
| Extended Washer Diameter: | 0.807 Inches Minimum And 0.817 Inches Maximum |
| Extended Washer Thickness: | 0.053 Inches Minimum And 0.073 Inches Maximum |
| Hole Diameter: | 0.050 Inches Minimum And 0.060 Inches Maximum |
| Grip Diameter: | 0.4360 Inches Minimum And 0.4370 Inches Maximum |
| Nominal Thread Diameter: | 0.438 Inches |
| Grip Length: | 0.990 Inches Minimum And 1.010 Inches Maximum |
| Hole Quantity: | 4 |
| Hole Type: | Drilled |
| Thread Quantity Per Inch: | 20 |
| Minimum Tensile Strength: | 220000 Pounds Per Square Inch |
| Hole Configuration Style: | Spline |
| Material: | Steel Comp Xm-13 Overall |
| Material Document And Classification: | Ams5629 Assn Std Single Material Response Overall |
| Surface Treatment: | Aluminum Overall And Chromate Overall |
| Surface Treatment Document And Classification: | Mil-c-83488,type 2 Class 3 Mil Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M753-7H16F> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.