

Description

Fastener Length: 2-3/32", Thread: 1/2-20, Thread Length: 49/64"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	ST3M753821
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-246-7462
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N ST3M753-8-21 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.762 Inches Minimum And 0.772 Inches Maximum
Fastener Length:	2.065 Inches Minimum And 2.095 Inches Maximum
Head Style:	Spline Extended Washer
Head Height:	0.358 Inches Minimum And 0.398 Inches Maximum
Width Between Flats:	0.547 Inches Minimum And 0.562 Inches Maximum
Extended Washer Diameter:	0.922 Inches Minimum And 0.932 Inches Maximum
Extended Washer Thickness:	0.062 Inches Minimum And 0.082 Inches Maximum
Grip Diameter:	0.4990 Inches Minimum And 0.4995 Inches Maximum
Nominal Thread Diameter:	0.500 Inches
Grip Length:	1.303 Inches Minimum And 1.323 Inches Maximum
Thread Quantity Per Inch:	20
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams5629 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Qq-p-35 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M753-8-21> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.