



Military-Fasteners.com

P/N ST3M753-8-36

Description

Fastener Length: 3-3/32", Thread: 1/2-20, Thread Length: 25/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M753836
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-371-3631
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



* See page 2 for technical characteristics

P/N ST3M753-8-36 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.787 Inches Nominal
Fastener Length:	3.103 Inches Nominal
Head Style:	Spline Extended Washer
Head Height:	0.440 Inches Minimum And 0.460 Inches Maximum
Extended Washer Diameter:	0.922 Inches Minimum And 0.932 Inches Maximum
Extended Washer Thickness:	0.084 Inches Minimum And 0.104 Inches Maximum
Grip Diameter:	0.4985 Inches Minimum And 0.4990 Inches Maximum
Head Minor Diameter:	0.547 Inches Minimum And 0.562 Inches Maximum
Nominal Thread Diameter:	0.500 Inches
Grip Length:	2.250 Inches Nominal
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	22000 Pounds Per Square Inch
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	Ams5629 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Mil-c-83488,ty 2,cl 3 Mil Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M753-8-36> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.