

Description

Fastener Length: 2-5/16", Thread: 1/4-28, Thread Length: 27/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | ST3M753861 |
| Minimum Qty (MOQ): | 1 |
| NSN: | 5306-01-095-5373 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N ST3M753-8-61 Specifications

| | |
|---|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.418 Inches Minimum And 0.422 Inches Maximum |
| Fastener Length: | 2.293 Inches Minimum And 2.313 Inches Maximum |
| Head Style: | Crowned Hexagon |
| Head Height: | 0.126 Inches Minimum And 0.141 Inches Maximum |
| Width Between Flats: | 0.488 Inches Nominal |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 1.875 Inches Minimum And 1.891 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Hardness Rating: | 36.0 Rockwell C Minimum Overall And 41.0 Rockwell C Maximum Overall |
| Material: | Steel Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Qq-p-416,type II,class 2 Fed Spec Single Treatment Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M753-8-61> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.