

Description

Fastener Length: 2-5/16", Thread: 1/4-28, Thread Length: 27/64

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M753861
Minimum Qty (MOQ):	1
NSN:	5306-01-095-5373
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N ST3M753-8-61 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.418 Inches Minimum And 0.422 Inches Maximum
Fastener Length:	2.293 Inches Minimum And 2.313 Inches Maximum
Head Style:	Crowned Hexagon
Head Height:	0.126 Inches Minimum And 0.141 Inches Maximum
Width Between Flats:	0.488 Inches Nominal
Nominal Thread Diameter:	0.250 Inches
Grip Length:	1.875 Inches Minimum And 1.891 Inches Maximum
Thread Quantity Per Inch:	28
Hardness Rating:	36.0 Rockwell C Minimum Overall And 41.0 Rockwell C Maximum Overall
Material:	Steel Overall
Surface Treatment:	Cadmium Overall
Surface Treatment Document And Classification:	Qq-p-416,type II,class 2 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this machine bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M753-8-61> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.