

**Description**

Fastener Length: 5-29/32", Thread: 1/2-20, Thread Length: 25/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

|                         |   |
|-------------------------|---|
| SKU / Model:            | ST3M753882                                |
| Minimum Qty (MOQ):      | 1 EA                                      |
| NSN:                    | 5306-01-127-3747                          |
| Schedule B:             | 7318.15.8085                              |
| ECCN:                   | EAR99                                     |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |

NO IMAGE  
AVAILABLE

## P/N ST3M753-8-82 Specifications

|   |  |
|---|--|
| <b>Thread Class:</b>                                  | 3a   |
| <b>Thread Direction:</b>                              | Right-hand   |
| <b>Thread Length:</b>                                 | 0.742 Inches Minimum And 0.792 Inches Maximum      |
| <b>Fastener Length:</b>                               | 5.877 Inches Minimum And 5.907 Inches Maximum      |
| <b>Head Style:</b>                                    | Spline Extended Washer                             |
| <b>Head Height:</b>                                   | 0.358 Inches Minimum And 0.398 Inches Maximum      |
| <b>Extended Washer Diameter:</b>                      | 0.922 Inches Minimum And 0.932 Inches Maximum      |
| <b>Extended Washer Thickness:</b>                     | 0.062 Inches Minimum And 0.082 Inches Maximum      |
| <b>Grip Diameter:</b>                                 | 0.4990 Inches Minimum And 0.4995 Inches Maximum    |
| <b>Head Minor Diameter:</b>                           | 0.547 Inches Minimum And 0.562 Inches Maximum      |
| <b>Nominal Thread Diameter:</b>                       | 0.500 Inches                                       |
| <b>Grip Length:</b>                                   | 5.115 Inches Minimum And 5.135 Inches Maximum      |
| <b>Thread Quantity Per Inch:</b>                      | 20   |
| <b>Minimum Tensile Strength:</b>                      | 220000 Pounds Per Square Inch                      |
| <b>Material:</b>                                      | Steel Comp Xm-13 Overall                           |
| <b>Material Document And Classification:</b>          | Ams 5629 Assn Std Single Material Response Overall |
| <b>Surface Treatment:</b>                             | Passivate Overall                                  |
| <b>Surface Treatment Document And Classification:</b> | Qq-p-35 Fed Spec Single Treatment Response Overall |
| <b>Thread Series Designator:</b>                      | Unjf   |

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M753-8-82> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.