

**Description**

Fastener Length: 5-29/32", Thread: 1/2-20, Thread Length: 25/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

**Additional Information**

SKU / Model:	ST3M753882
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-127-3747
Schedule B:	7318.15.8085
ECCN:	EAR99
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE  
AVAILABLE

\* See page 2 for technical characteristics

## P/N ST3M753-8-82 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.742 Inches Minimum And 0.792 Inches Maximum
<b>Fastener Length:</b>	5.877 Inches Minimum And 5.907 Inches Maximum
<b>Head Style:</b>	Spline Extended Washer
<b>Head Height:</b>	0.358 Inches Minimum And 0.398 Inches Maximum
<b>Extended Washer Diameter:</b>	0.922 Inches Minimum And 0.932 Inches Maximum
<b>Extended Washer Thickness:</b>	0.062 Inches Minimum And 0.082 Inches Maximum
<b>Grip Diameter:</b>	0.4990 Inches Minimum And 0.4995 Inches Maximum
<b>Head Minor Diameter:</b>	0.547 Inches Minimum And 0.562 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.500 Inches
<b>Grip Length:</b>	5.115 Inches Minimum And 5.135 Inches Maximum
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	220000 Pounds Per Square Inch
<b>Material:</b>	Steel Comp Xm-13 Overall
<b>Material Document And Classification:</b>	Ams 5629 Assn Std Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M753-8-82> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.