

## Description

Fastener Length: 1-29/32", Hole Diameter: 3/64", Thread: 3/8-20, Thread Length: 23/32"

\* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

## Additional Information

SKU / Model:	ST3M753L7H19
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-368-8043
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)



## P/N ST3M753L7H19 Specifications

<b>Thread Class:</b>	3a
<b>Thread Direction:</b>	Right-hand
<b>Thread Length:</b>	0.680 Inches Minimum And 0.730 Inches Maximum
<b>Fastener Length:</b>	1.877 Inches Minimum And 1.907 Inches Maximum
<b>Head Style:</b>	Spline Extended Washer
<b>Head Height:</b>	0.320 Inches Minimum And 0.340 Inches Maximum
<b>Extended Washer Diameter:</b>	0.807 Inches Minimum And 0.817 Inches Maximum
<b>Extended Washer Thickness:</b>	0.053 Inches Minimum And 0.073 Inches Maximum
<b>Hole Diameter:</b>	0.050 Inches Minimum And 0.060 Inches Maximum
<b>Grip Diameter:</b>	0.4365 Inches Minimum And 0.4370 Inches Maximum
<b>Head Minor Diameter:</b>	0.340 Inches Minimum And 0.485 Inches Maximum
<b>Nominal Thread Diameter:</b>	0.437 Inches
<b>Grip Length:</b>	1.177 Inches Minimum And 1.197 Inches Maximum
<b>Hole Quantity:</b>	4
<b>Hole Type:</b>	Drilled
<b>Thread Quantity Per Inch:</b>	20
<b>Minimum Tensile Strength:</b>	220000 Pounds Per Square Inch
<b>Hole Configuration Style:</b>	Spline
<b>Material:</b>	Steel Comp Xm-13 Overall
<b>Material Document And Classification:</b>	Ams5629 Fed Spec Single Material Response Overall
<b>Surface Treatment:</b>	Passivate Overall
<b>Surface Treatment Document And Classification:</b>	Qq-p-35 Fed Spec Single Treatment Response Overall
<b>Thread Series Designator:</b>	Unjf

## How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M753L7H19> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.