

Description

Fastener Length: 2-19/32", Hole Diameter: 3/64", Thread: 7/16-20, Thread Length: 23/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M753L7H30
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-368-8047
Schedule B:	7318.15.8085
ECCN:	9A991
National Motor Freight:	093486, Bolts,nuts Or Screws, Noi (sub 3)

NO IMAGE
AVAILABLE

P/N ST3M753L7H30 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.680 Inches Minimum And 0.730 Inches Maximum
Fastener Length:	2.565 Inches Minimum And 2.595 Inches Maximum
Head Style:	Spline Extended Washer
Head Height:	0.383 Inches Minimum And 0.403 Inches Maximum
Extended Washer Diameter:	0.807 Inches Minimum And 0.817 Inches Maximum
Extended Washer Thickness:	0.053 Inches Minimum
Hole Diameter:	0.050 Inches Minimum And 0.060 Inches Maximum
Grip Diameter:	0.4365 Inches Minimum And 0.4370 Inches Maximum
Head Minor Diameter:	0.514 Inches Minimum And 0.521 Inches Maximum
Nominal Thread Diameter:	0.438 Inches
Grip Length:	1.865 Inches Minimum And 1.885 Inches Maximum
Hole Quantity:	4
Hole Type:	Drilled
Features Provided:	Dry Film Lubricant
Thread Quantity Per Inch:	20
Minimum Tensile Strength:	220000 Pounds Per Square Inch
Hole Configuration Style:	Spline
Material:	Steel Comp Xm-13 Overall
Material Document And Classification:	As8879 Assn Std Single Material Response Overall
Surface Treatment:	Passivate Overall
Surface Treatment Document And Classification:	Ams2700 Fed Spec Single Treatment Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M753L7H30> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.