

Description

Thread Size: 1/4"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

SKU / Model:	ST3M7735
Minimum Qty (MOQ):	5 EA
NSN:	5320-01-132-9858
Schedule B:	7616.10.9090
ECCN:	EAR99
National Motor Freight:	106510, Rivets I / S Plain / Galvanized Etc

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N ST3M773-5 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.532 Inches Minimum And 0.538 Inches Maximum
Collar Overall Height:	0.652 Inches Minimum And 0.672 Inches Maximum
Lubrication:	Solid Film And Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.330 Inches Minimum And 0.336 Inches Maximum
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.312 Inches
Collar Style:	Threaded (break Off) Type
Material:	Steel Comp 630 Overall
Material Document And Classification:	Ams 5643 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/ST3M773-5 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.