

## P/N ST3M773-5

### **Description**

Thread Size: 1/4"

\* Manufacturer certifications are shipped with your order FREE of charge

### Order this part online

#### **Additional Information**

SKU / Model: ST3M7735

Minimum Qty (MOQ): 5 EA

NSN: 5320-01-132-9858

Schedule B: 7616.10.9090

ECCN: EAR99

National Motor Freight: 106510, Rivets I / S Plain / Galvanized Etc



<sup>\*</sup> See page 2 for technical characteristics

# P/N ST3M773-5 Specifications

Thread Class:	3b
Thread Direction:	Right-hand
Collar Outside Diameter:	0.532 Inches Minimum And 0.538 Inches Maximum
Collar Overall Height:	0.652 Inches Minimum And 0.672 Inches Maximum
Lubrication:	Solid Film And Cetyl Alcohol, Spec 305, Hi-shear Corp
Collar Inside Diameter:	0.330 Inches Minimum And 0.336 Inches Maximum
Thread Quantity Per Inch:	24
Nominal Thread Size:	0.312 Inches
Collar Style:	Threaded (break Off) Type
Material:	Steel Comp 630 Overall
Material Document And Classification:	Ams 5643 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

## **How to Order**

Order this collar from our inventory online by visiting <a href="https://military-fasteners.com/collars/pin\_rivet+collars/ST3M773-5">https://military-fasteners.com/collars/pin\_rivet+collars/ST3M773-5</a> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out <a href="here">here</a> to complete your order.