

Description

Thread Size: 1/2"

* Manufacturer certifications are shipped with your order FREE of charge[Order this part online](#)**Additional Information**

| | |
|-------------------------|---|
| SKU / Model: | ST3M7737 |
| Minimum Qty (MOQ): | 1 EA |
| NSN: | 5320-01-340-9111 |
| Schedule B: | 7616.10.9090 |
| ECCN: | EAR99 |
| National Motor Freight: | 106510, Rivets I / S Plain / Galvanized Etc |

NO IMAGE
AVAILABLE

* See page 2 for technical characteristics

P/N ST3M773-7 Specifications

| | |
|--|---|
| Thread Class: | 3b |
| Thread Direction: | Right-hand |
| Collar Outside Diameter: | 0.737 Inches Minimum And 0.743 Inches Maximum |
| Collar Overall Height: | 0.842 Inches Minimum And 0.862 Inches Maximum |
| Lubrication: | Solid Film And Cetyl Alcohol, Spec 305, Hi-shear Corp |
| Collar Inside Diameter: | 0.460 Inches Minimum And 0.466 Inches Maximum |
| Thread Quantity Per Inch: | 20 |
| Nominal Thread Size: | 0.438 Inches |
| Collar Style: | Threaded (break Off) Type |
| Material: | Steel Comp 630 Overall |
| Material Document And Classification: | Ams 5643 Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this collar from our inventory online by visiting https://military-fasteners.com/collars/pin_rivet+collars/ST3M773-7 and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.