

Description

Fastener Length: 13/16", Thread: 10-32, Thread Length: 7/16

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M794V36A
Minimum Qty (MOQ):	5
NSN:	5305-01-197-3511
Schedule B:	8108.90.3060
ECCN:	EAR99
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N ST3M794V3-6A Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.380 Inches Minimum And 0.447 Inches Maximum
Fastener Length:	0.765 Inches Minimum And 0.812 Inches Maximum
Head Style:	Flat Countersunk Undercut
Head Diameter:	0.4625 Inches Minimum And 0.4672 Inches Maximum
Head Height:	0.0800 Inches Minimum And 0.0820 Inches Maximum
Grip Diameter:	0.1890 Inches Minimum And 0.1895 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.190 Inches
Grip Length:	0.365 Inches Minimum And 0.385 Inches Maximum
Thread Quantity Per Inch:	32
Countersink Angle:	100.0 Degrees Nominal
Surface Finish:	32.0 Microinches Bearing Surface Of Head
Surface Finish:	32.0 Microinches Grip
Surface Finish:	32.0 Microinches Threads
Special Features:	Furnished With O9ring
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4967 6al-4v Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this close tolerance scrwe from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/ST3M794V3-6A> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.