

Description

Fastener Length: 3-7/16", Thread: 1--12, Thread Length: 1-1/4"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M833V16T35
Minimum Qty (MOQ):	1 EA
NSN:	5306-01-169-2904
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi

NO IMAGE
AVAILABLE

P/N ST3M833V16T35 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	1.261 Inches Nominal
Fastener Length:	3.449 Inches Nominal
Head Style:	Hexagon
Head Height:	0.471 Inches Nominal
Width Between Flats:	1.427 Inches Minimum And 1.470 Inches Maximum
Locking Feature:	Detent Ball Threads
Grip Diameter:	0.9985 Inches Minimum And 0.9990 Inches Maximum
Shank Unthreaded Hole Diameter:	0.141 Inches Minimum First Hole And 0.151 Inches Maximum First Hole
Nominal Thread Diameter:	1.000 Inches
Grip Length:	2.188 Inches Nominal
Thread Quantity Per Inch:	12
Distance From Head Largest Bearing Surface To Shank Hole Center:	2.819 Inches Nominal First Hole
Special Features:	Furnished With Inhibitor. Material Comp 6al-4v
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams 4967 Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/ST3M833V16T35> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.