

Description

Fastener Length: 39/64", Thread: 1/4-28, Thread Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

SKU / Model:	ST3M86642
Minimum Qty (MOQ):	5 EA
NSN:	5305-01-170-6198
Schedule B:	8108.90.3060
ECCN:	9A991
National Motor Freight:	136500, Metal Noi / Metal Alloys Noi



* See page 2 for technical characteristics

P/N ST3M866-4-2 Specifications

Thread Class:	3a
Thread Direction:	Right-hand
Thread Length:	0.344 Inches Minimum And 0.411 Inches Maximum
Fastener Length:	0.572 Inches Minimum And 0.619 Inches Maximum
Head Style:	Pan No. 2
Head Diameter:	0.4975 Inches Minimum And 0.4980 Inches Maximum
Head Height:	0.140 Inches Minimum And 0.150 Inches Maximum
Grip Diameter:	0.2490 Inches Minimum And 0.2495 Inches Maximum
Internal Drive Style:	High-torque
Nominal Thread Diameter:	0.250 Inches
Grip Length:	0.208 Inches Minimum And 0.228 Inches Maximum
Thread Quantity Per Inch:	28
Material:	Titanium Alloy Overall
Material Document And Classification:	Ams4967,comp 6al-4v Assn Std Single Material Response Overall
Thread Series Designator:	Unjf

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/ST3M866-4-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.