

Description

Fastener Length: 39/64", Thread: 1/4-28, Thread Length: 13/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|--------------------------------------|
| SKU / Model: | ST3M86642 |
| Minimum Qty (MOQ): | 5 EA |
| NSN: | 5305-01-170-6198 |
| Schedule B: | 8108.90.3060 |
| ECCN: | 9A991 |
| National Motor Freight: | 136500, Metal Noi / Metal Alloys Noi |

NO IMAGE
AVAILABLE

P/N ST3M866-4-2 Specifications

| | |
|--|---|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.344 Inches Minimum And 0.411 Inches Maximum |
| Fastener Length: | 0.572 Inches Minimum And 0.619 Inches Maximum |
| Head Style: | Pan No. 2 |
| Head Diameter: | 0.4975 Inches Minimum And 0.4980 Inches Maximum |
| Head Height: | 0.140 Inches Minimum And 0.150 Inches Maximum |
| Grip Diameter: | 0.2490 Inches Minimum And 0.2495 Inches Maximum |
| Internal Drive Style: | High-torque |
| Nominal Thread Diameter: | 0.250 Inches |
| Grip Length: | 0.208 Inches Minimum And 0.228 Inches Maximum |
| Thread Quantity Per Inch: | 28 |
| Material: | Titanium Alloy Overall |
| Material Document And Classification: | Ams4967,comp 6al-4v Assn Std Single Material Response Overall |
| Thread Series Designator: | Unjf |

How to Order

Order this screw from our inventory online by visiting <https://military-fasteners.com/screws/close+tolerance+screws/ST3M866-4-2> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.