



Military-Fasteners.com

P/N STD2180D35

Description

Fastener Length: 41/64", Thread: 10-32A, Thread Length: 7/32"

* Manufacturer certifications are shipped with your order FREE of charge

Order this part online

Additional Information

| | |
|-------------------------|---|
| SKU / Model: | STD2180D35 |
| Minimum Qty (MOQ): | 15 EA |
| NSN: | 5305-00-467-7553 |
| Schedule B: | 7318.15.8085 |
| ECCN: | EAR99 |
| National Motor Freight: | 093486, Bolts,nuts Or Screws, Noi (sub 3) |



* See page 2 for technical characteristics

P/N STD2180D35 Specifications

| | |
|---|--|
| Thread Class: | 3a |
| Thread Direction: | Right-hand |
| Thread Length: | 0.220 Inches Nominal |
| Fastener Length: | 0.633 Inches Minimum And 0.653 Inches Maximum |
| Head Style: | Flat Countersunk |
| Head Diameter: | 0.337 Inches Minimum And 0.387 Inches Maximum |
| Grip Diameter: | 0.1898 Inches Minimum And 0.1904 Inches Maximum |
| Internal Drive Style: | High-torque |
| Nominal Thread Diameter: | 0.190 Inches |
| Grip Length: | 0.350 Inches Minimum And 0.413 Inches Maximum |
| Thread Quantity Per Inch: | 32a |
| Countersink Angle: | 99.0 Degrees Minimum And 101.0 Degrees Maximum |
| Material: | Titanium Alloy Uns R56400 Overall |
| Material Document And Classification: | Ams 4967 Assn Std Single Material Response Overall |
| Surface Treatment: | Cadmium Overall |
| Surface Treatment Document And Classification: | Std 2167 Cagec 99995 Mfr Ref Single Treatment Response Overall |
| Thread Series Designator: | Unf |

How to Order

Order this bolt from our inventory online by visiting <https://military-fasteners.com/bolts/machine+bolts/STD2180D35> and selecting the quantity you want then click "add to cart". Once items are in your cart you can check out [here](#) to complete your order.